

客户：

Technical drawing of a mechanical part, likely a bracket or support, showing dimensions and callouts. The drawing includes a cross-section view and a top view.

Dimensions:

- Overall width: $8.35_{-0.12}^0$
- Inner width: $6.3_{-0.12}^0$
- Top flange thickness: $2_{-0.15}^0$
- Top flange radius: $R2.55$
- Top flange outer diameter: $\phi 13_{-0.008}^0$
- Top flange inner diameter: $\phi 4_{-0.012}^0$
- Top flange hole diameter: $2_{-0.15}^0$
- Top flange hole position: $2_{-0.15}^0$
- Top flange hole diameter: $\phi 6_{-0.01}^0$
- Top flange hole position: 5.2 ± 0.03
- Top flange hole diameter: $\phi 11 \pm 0.02$

Callouts:

- ①: Top flange
- ②: Top flange hole
- ③: Top flange hole
- ④: Top flange hole
- ⑤: Top flange hole

单位: mm

						附注:
标记	处数	修订前内容		修订者	修订日期	
NO.	部 件	材 质	数 量	备 注	基本额定静负荷: COr: 689 N	
1	内 圈	GCr15	1		基本额定动负荷: Cr: 1469 N	
2	外 圈	GCr15	1		径向游隙:	
3	钢 球	GCr15	2*7-Ø2.0		C0 0.002-0.013	
4	保持架	NYLON	2		精度等级: P0	
5	密封圈	NBR	2		客户料号:	
					料号: Q594W8.35/6.3-2RS-n-SB	
制 图		审 核		承 认		图号: QAJ/TR25102
						NBK 宁波庄宏亿轴承有限公司
制图日期				2025年8月25日		